

AOC®

i2769Vm



Cabinet Color	Glossy Black Bezel, Base; Hairline texture on Bottom Back Cover	
Panel	TFT Active Matrix LCD, LED Backlight 27" Widescreen, 16:9 Aspect Ratio 27" Viewable Image Size, Diagonal	
Pixel Pitch	0.311(H) x 0.311(V)mm	
Display Area	597.888(H) x 336.312(V)	
Brightness	250 cd/m2 (typ)	
Contrast Ratio	50,000,000:1 (dynamic)	
Response Time	5ms	
Viewing Angle	Horizontal: 178 Degrees (CR>10) Vertical: 178 Degrees (CR>10)	
Scanning Frequency	Horizontal: 30K~83KHz Vertical: 50~75 Hz	
Pixel Frequency	170MHz	
Maximum Resolution	1920x1080@60Hz	
Recommended Resolution	1920x1080@60Hz	
Supported Resolutions	640x480@60/72/75Hz 800x600@56/60/72/75Hz 832x624@75Hz 1024x768@60/70/75Hz 1280x1024@60/75Hz 1280x960@60Hz 1440x900@60Hz 1680x1050@60Hz 1920x1080@60Hz	
Color	16.7M	
Signal Input	Analog: 0.7Vp-p(standard), 75 OHM, Positive	
Digital Input	HDMI with HDCP*, HDMI (MHL), Display Port	
Connectors	Analog RGB Signal: 15-pin D-sub Male Digital Signal: 19-pin HDMI, HDMI (MHL), Display Port	
Power Source	Universal 100~240VAC, 50/60Hz	
Power Consumption	On: 35 Watts (typical), Standby: <0.5W	
Plug & Play	DDC/2B, DDC/CI	
User Control	Left/Clear Vision, Right/Volume, Source/Auto/Exit, Menu/Enter, Power	
OSD Languages	16 Languages including English, French and Spanish	
Regulations	FCC, cCSAus, CE, TUV/S, EPA Energy Star, RoHS, Windows 7/8	
Built-in Speakers	2 Watts * 2	
Other Features	Extra slim, Bezel-less , IPS panel, MHL compatible for Android Smartphone/Tablet, User Friendly Graphical OSD Menu; VESA 75mm Wall Mount Compliant*, Windows 8 compatible	
Dimensions (WxHxD mm)	Monitor: 622x449x130 , Carton: 710x538x159	
Dimensions (WxHxD inches)	Monitor:24.5x17.7x5.1 , Carton: 28.0x21.2x6.3	
Weight	11.0 lbs (5.0 Kg) Net 16.1lbs (7.3 Kg) Gross	
Loading Qty w/pallet	20' = 360 pcs.; 40' Std = 756 pcs.	
UPC Code	685417064281	

Note: Specifications are subject to change without notice. *High-bandwidth Digital Content Protection: Enables viewing of High-Definition contents.
A01/13