# YOUR NEW ADDITION imageCLASS MF729Cx

**WORKHORSE PLUS RANGE** Multifunction Laser Printer



A colour laser multifunction Laser Printer that does it all. The MF729Cx features convenient Duplex printing and Duplex Scanning, SEND ability and convenient Wi-Fi connectivity.

The MF729Cx is the next generation of small office printing. Ideal for use with mobile devices, the MF729Cx is compatible with Apple AirPrint, Google Cloud Print, NFC & Canon's own Mobile Printing App. It also supports UFR II, PCL & PS3 for ultimate compatibility into any printing environment. The imageCLASS MF729Cx allows you to scan your documents quickly and easily for direct distribution via email, network file server, FTP server or USB key. Save the environment while you save money with Duplex printing and Duplex Scanning – and now with eRDS for automatic meter reads.

#### **Key Features**

#### All-in-One cartridges Toner Cartridges

• The MF729Cx utilises a drum cartridge in which an "Intermediate Transfer Unit", "Photosensitive Drum", and "Waste Toner Container" that are normally individual consumables, are all combined, meaning less consumables to stock and less fuss.

#### Low Power Consumption and **Quick Start Up**

 Canon's unique On-Demand Fixing System allows for lightning fast 1st prints. The MF729Cx is also energy star certified and consumes only 1 watt of power in sleep mode, so you not only

save on your electricity bill but also the environment too.

#### As a Laser Printer

- Up to 20 pages per minute for colour and mono with 14.5 seconds to first print
- 600 x 600 dpi laser print resolution (enhanced to 2400 x 600 dpi by smoothing technology)
- 1 GB Memory
- Auto duplex for easy double sided printing and copying

#### As a Fax Machine

• 33.6 Kbps Super G3 fax – up to 3 seconds per page fax transmission

- Huge fax memory of up to 512 pages to ensure there are no lost messages
- 50-page Automatic Document Feeder for fast, unattended copying and faxing

#### As a Scanner

• Up to 600 x 600 dpi (optical) and 9600 x 9600 dpi (interpolated) colour scanning resolution for sharp images

#### As a Copier

- ·20 copies per minute makes up to 99 copies at a time
- Reduction/enlargement ranges of 25% to 400%; Electronic collating; reserve copy.

Х

# **Quality images**

High print resolution (20 ppm, 600 x 600 dpi / up to 2400 x 600 dpi enhanced) @ 20 ppm

#### **High Quality Copying**

Laser copy quality 600 x 600 dpi @ 20 cpm

#### **Duplexing Automatic Document Feeder**

50-page Duplexing Automatic Document Feeder (DADF) for easy double sided printing and copying

#### **Integrated Network**

Integrated network for workgroup printing

CERTIFIED
 $\square$

#### **Wi-Fi Network Connectivity**

Easy set-up mode will search for access points to connect to - ensuring trouble free network connections.



## **Google Cloud Print**

Compatible with Apple AirPrint & Google Cloud Print, for direct printing from network enabled mobile devices

#### **Quality Scanning**



CCD scanning at 600 x 600 dpi (optical) and 9600 x 9600 dpi

#### (interpolated) **Toner Gauge**

Useful toner gauge function to confirm remaining toner quantity

### PS3, PCL & UFR II

PCL Combining the flexibility of PS3, PCL and the advanced functionality of UFR II to provide the best customer experience

#### Laser Printers

Canon laser printers combine a range of features and technologies to deliver fast, high quality and reliable printing. So, if you are looking to create professional business documents while reducing your running costs, Canon lasers fit the bill.

Subject to change without notice





# imageCLASS MF729Cx Workhorse Plus Range – Multifunction Laser Printer

Print Specifications	
Printing Method	Colour Laser
Print Speed <sup>1</sup>	Simplex: Colour/B&W A4: up to 20/20 ppm (pages per minute) Duplex: Colour/B&W A4: up to 10/10 ppm (pages per minute)
Print Resolution	600x600 dpi equivalent (2400 $x600 dpi$ with Image Refinement)
Warm up Time	23 sec or less from power-on
First Printout Time	Black/Colour: Approx. 16.4/16.7 sec (A4)
Recovery Time	Approx. 8 sec
Print Language/Emulation	Standard: UFR II LT (Host Based) / PCL6 (5e,XL) PS3
Direct Print	Print File format: JPEG, TIFF (via USB Host v1.1)
Print Features	Poster, Booklet, Watermark, Page Composer, Toner Saver
Copier Specifications	
Copy Speed	Simplex: Colour/B&W A4: up to 20/20 ppm (pages per minute) Duplex: Colour/B&W A4: up to 10/10 ppm (pages per minute)
Copy Resolution	Up to 600 x 600 dpi
First Copy Time	Colour/B&W: Approx. 15.5/16.2sec (A4)
Maximum Number of Copies	Up to 99 copies
Reduce/Enlargement	25 - 400% in 1% increments
Copy Features	Frame Erase, Memory Sort, 2 on 1, 4 on 1, ID Card Copy
Scan Specifications	
Scan Resolution	Optical: Up to 600 x 600 dpi Driver (digital): Up to 9600 x 9600 dpi
Colour Depth	24-bit
Duplex Scan	Yes
Pull / Push Scan (via MF ToolBox)	Yes, USB and Network, Scan to USB
Scan Features	TWAIN, WIA (Scan Driver Compatibility)
File Format	SMB : JPEG, TIFF, PDF, Compact PDF E-mail : PDF, Compact PDF
Fax Specifications	
Modem Speed	Up to 33.6 Kbps
Fax Resolution	Up to 406 x 391 dpi
Memory Capacity <sup>1</sup>	Up to 512 pages (Speed Dial Up to 181 dials)
Duplex Fax (TX)	Yes
Memory Backup	Permanent fax memory backup. ( Backup with flash memory)
FAX Features	FAX Forwarding, Dual Access, Remote Reception, PC FAX(TX only), DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports
Paper Handling Specifica	tions
Auto Document Feeder	50 sheets (80gsm)
Paper Input	Standard: Plain Paper (60-163g/m²):250-sheet cassette plus 50-sheet multipurpose tray Optional: Plain Paper (80g/m²): 250-sheet
Paper Output	125 sheets (face down)
Paper Sizes	Standard & Optional Cassette: A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, BOFFICIO, M-OFFICIO, GLTR, GLGL, FLS, AFLS, indLGL 16K, Postcard, Postcard without folding line, Envelope: COM10, Monarch, C5, B5, DL(US), Custom(Min. 76.2 x 127mm to Max. 215.9 x 355.6mm)
Paper Types	Plain, heavy, Recycled, Colour, Coated, Transparency, Label, Index, Envelope
Paper Weight	Std. cassette / Opt. cassette: 60 to 163 g/m² Std. MP tray: 60 to 220 g/m²



LAS-2YOS-1 – 3 year Extended Onsite Service & Support card

canon.com.au/business Follow us on Twitter @CanonBusinessAU 1800 444 199 3822-v1-08/15



Connectivity & Software	
Standard Interface(s)	Wired: USB Device 2.0 High-Speed, 10/100 Base-T Ethernet (Network), Wireless: Wi-Fi 802.11b/g/n
Network Security	Wired: IP/Mac address filtering, HTTPS, SNMPv3, IEEE802.1x, Wireless: WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES), 802.1x (LEAP, EAP-FAST, PEAP, EAP-TLS, EAP-TLS)
One-Push Wireless Config	WPS, AOSS
OS Compatibility	Print/FAX/Scan Drivers: Windows® 8, Windows® 7, Windows Server® 2012, Windows Server® 2008 R2, Windows Server® 2008, Windows Vista®, Windows Server® 2003, Windows® XP, Mac® OS X 10.5.8 & up, Linux <sup>2</sup> Remote UI (operating environment): IE 7.0 or higher, Safari 3.2.1 or higher
Security & Other Feature	25
Security Function	Native Secured Print, IEEE802.1x, SNMPv3, HTTPS, IPSEC
Cloud/Mobile Print	Google Cloud Print, Apple AirPrint, LDAP
General Specifications	
Memory	Standard/Max.: 1GB / 1GB
LCD Display	3.5 inch Colour Touch Screen
Dimensions (W x D x H)	434mm x 484mm x 479mm
Weight	31.0 kg (w CRG)
Power Consumption	Maximum consumption: 1,200 W or less Operation: Approx. 450 W Standby: Approx. 23 W Sleep: Approx. 1.0 W /2.0 W (wireless)
Noise Levels	During operation: Sound pressure Level (Bystander's position): 50dB in Colour Printing 49dB in B/W Printing (reference value) During operation: Sound pressure Level (Bystander's position): 67dB in Colour Printing, 66dB in B/W Printing (reference value) During standby: Sound pressure Level (Bystander's position) : Inaudible <sup>43</sup> (Reference Value)
Operating Environment Humidity	20% to 80% RH (no condensation)
Toner	
Cartridges <sup>4</sup>	CART418BK: 3,400 pages / CART418C / M / Y 2,900 pages

1. Based on ITU-T #1 Chart (standard mode).

2. Linux support printing only.

"Inaudible" means each sound pressure level at bystander's position is less than the absolute criterion value about backgroundnoise of ISO7779.
In compliance with ISO/IEC 19798

Subject to change without notice.

