



Designed for the most demanding office environment with network capabilities, Brother's monochrome office laser printers HL-5350DN and HL-5380DN achieve printouts at high print speed. Its high print resolution produces professional-looking business documents. With a built-in duplex function, both printers save paper for double-sided printing. These printers are cost effective with maximum drum and toner usage. You can always be sure of optimum performance at work with Brother at your side.

# High Speed Printing with Maximum Performance

Both printers have a high print speed of up to 30 ppm for single page printing and up to 13 ppm<sup>2</sup> for duplex print. With a true 1,200 x 1,200 dpi resolution3, the HL-5350DN & HL-5380DN ensure your printouts are professional-looking for your business needs.

### **Low Operating Costs**

With a separate toner and drum technology, HL-5350DN and HL-5380DN reduce your total cost of ownership. As the drum cartridge is being maximised after several toner cartridges are depleted, costs are reduced to the minimal. HL-5350DN is shipped with a standard toner with up to 3,000 print papers<sup>1</sup> while HL-5380DN comes with a high yield toner with up to 8,000 print pages1.

#### **Environmental Friendly with Cost Savings**

The HL-5350DN & HL-5380DN have a built-in duplex function to save paper by printing on both sides of the paper automatically. In addition, its N in 1 printing and booklet printing features enable you to save on paper. The environmental-friendly HL-5350DN & HL-5380DN are Energy Star compliant to ensure minimal usage on electricity and reduce your bills.

<sup>&</sup>lt;sup>2</sup> 13 sides per minute, 6.5 sheets per minute (A4) <sup>3</sup> Using 1,200 dpi setting (1,200 x 1,200 dpi), the print speed will be compromised



# **Compatible to Suit All Business Environments**

With flexible support on all major operating systems including Microsoft® Windows, Macintosh® and Linux, business users will find it a breeze to print with the HL-5350DN & HL-5380DN.

#### **Network Connectivity for Sharing of Resources**

Equipped with an Ethernet port and an integrated 10/100 Base-TX network card, the sharing of resources is possible in a small workgroup to optimise IT investment. With the support of advanced network protocols such as APIPA4 and DHCP5, network connectivity is greatly simplified.

- <sup>4</sup> APIPA Automatic Private IP Addressing
   <sup>5</sup> DHCP Dynamic Host Configuration Protocol



## Advanced networking features for higher returns on investment

### Network management tools for efficient IT support

Depending on the size of your network, Brother has an array of network management tools to choose from to best-fit your requirement. The BRAdmin Professional Software for administering LAN connected devices, or the Enterprise edition Web BRAdmin for WAN is available for efficient network management and client support.

Brother's easy-to-use network management tools give you complete control of your networking environment. Attention required such as low toner levels, mechanical attention or print job errors on the machine are automatically reported to the network administor via email for quick rectification.



What's more, you can even customise the degree of error settings that you would like to be alerted on. As a result, you now have the freedom of viewing and adjusting the printer or network settings, without leaving your desk.

## Supports IPv4 & IPv6 protocols to safeguard investment in the future.

The current IPv4 as well as the upcoming IPv6 protocols are being supported to safeguard your investment even in the future, and handle any transition period effectively without any upgrading costs.





CENTRAL Cotrangly Perit Speed Display (4)			No.	ton.
Secretary   Deptet Mod   Dept			HL-5350DN	HL-5380DN
Pint Special   Dip to 1 Dip				
First Print Out Time			Up to 30	ppm¹
Repolution 1,200 dpi, Holl200 (2,400 x 500 dpi,	First Print Out Time	Dapiox (14)		
Memory	Resolution		1,200 dpi, HQ1200 (2,400 $ imes$ 600 dpi), $6$ 00 dpi, $3$ 00 dpi	
Interface Interf				
Encident Forts   PQL 50				
Resident Fortis  PROJET  PROJET STATE  BRITTON				
Display		PCL®6		
Cointois  Euttons  Full Horis	i iosiaciii i oino			
Buttons  But				
Buttons  Go., Job Cancel  Go., Job Cancel, Set, Back, Secure Print, Scroll  PAPER HANDLING  Berger Input  Gosted on Stylen paper)  Multi-Purcose Tiny  Face Down  Tinn Paper, Plain Paper, Bond Paper, Recycled Paper, Envelopes, Labels,  Whiti-purpose Tray  Multi-purpose Tray  Optional Tray  Multi-purpose	Controls	LED		Data
PAPER HANDUNO Paper Input (Based on 80 pan paper) Multi-Purpose Tray Control (Based on 80 pan) Multi-Purpose Tray Control (Based on 80 pan) Paper Option (Based on 80 pan) Paper Option (Based on 80 pan) Paper Tray (Standard) Multi-Purpose Tray Control (Based on 80 pan) Multi-Purpose Tray Duplox Printing Multi-Purpose Tray Multi-Purpose	Puttono			Co. Joh Concol Sot Book
Raper Input (Based on 80 January 1 250 sheets (Based on 180 January 1 250 January 1 25	DULLOTIS		Go, Job Cancel	
(Básed on 80gsm paper) Optional Paper Tray Optional Paper Tray Optional Paper Tray Optional Paper Tray Paper Output Face Up Fa	PAPER HANDLING			
Paper Output Paper Tray				
Paper Output   Sales	(Based on 80gsm paper)			
Blased on 80gsm paper	Damas Outrout			
Media Types  Media Types  Media Types  Media Types  Media Types  Media Types  Media Weights  Paper Tray (Standard) Multi-purpose Tray  Media Weights  Paper Tray (Standard / Optional) Media Weights  Paper Tray (Standard / Optional) Media Weights  Paper Tray (Standard / Optional) Media Sizes  Paper Tray (Standard / Optional) Media Sizes  Paper Tray (Standard) Multi-purpose Tray Optional Tray  Media Sizes  Paper Tray (Standard) Multi-purpose Tray Optional Tray Auto Duplox Printing  Media Sizes  Windows*				
Media Types    Paper Tray (Standard)   Multi-purpose Tray   Multi-purpose Tray   Multi-purpose Tray   Thin Paper, Plain Paper, Evel Paper, Bond Paper, Recycled Paper, Errorepose, Labels, and Transparencies (Up to 10 sheets)   Thin Paper, Plain Paper, Bond Paper, Recycled Paper, Errorepose, Labels, and Transparencies (Up to 10 sheets)   Thin Paper, Plain Paper, Bond Paper, Bon		1 200 001111	130 816	
Multi-purpose Tray Optional Tray Optional Tray Media Weights Paper Tray (Standard / Optional) Multi-purpose Tray Optional Tray Optional Tray At 150 Multi-purpose Tray Server 2003 Ref Edition, Server 2003 At 150 Age environment)  NETWORK  NETWORK  Professional Xel Edition, Vera Professional Xel Edition, Vera Professional Xel Edition, Vera Professional Xel Edition, Server 2008 Approx. Appr		Paper Tray (Standard)	Thin Paper Plain Paper Rond Paper Recycles	Paper Transparencies (Up to 10 sheets)
Media Weights   Paper Tray (Standard / Optional)   Multi-purpose Tray   Go. 1-63g/m2   Go. 1-63g	Wedia Types	Multi-purpose Tray	Thin Paper, Plain Paper, Thick Paper, Bond Paper, Recycled Paper, Envelopes, Labels,	
Multi-purpose Tray Duplex Printing A4, ISOBS, A5, SLOng Edge), ISOB6, A6, Executive Multi-purpose Tray Optional Tray Auto Duplex Printing A4, ISOB5, A5, ISOB6, Expective Auto Duplex Printing  SOFTWARE  Windows® Windows® Windows® Windows® Windows® A2, ISOB6, A5, ISOB6, Executive Auto Duplex Printing  Macintosh® Linux  Windows® Windows® Windows® Windows® A2, ISOB6, Executive Auto Duplex Printing  Macintosh® Linux  Windows® Windows® Windows® Windows® A2, ISOB6, Executive AUTO Duplex Printing  Macintosh® Linux  Windows® Windows® Windows® Windows® A2, ISOB6, Executive AUTO Duplex Printing System (A6, X44 entroment)  NETWORK  Protocols  NETWORK  Protocols  IPv4 (Default)  NETWORK  Protocols  IPv4 (Default)  APP, RARB, BOOTE, DHCP, APIPA/Auto IP) Windows Macintonent DINS Resolver, mDNS, LIMMR responder, LEPKLPD, Cautem Raw FootProttotio, IPPA/PPS, FTP Server, TELINET Server, SUTLIS, ITTLE client and server, SUTLIS, ITTLE responder, WebServicesPrint  Web BRAdmin Professional 3 Web BRAdmin Web Based Management BRAdmin Light Strate Web Based Management BRAdmin Light Strate Windows Mill (Modows utility for printer and server suffer Client, APOP, POP before SWITP, SMITP-AUTH, SMMPVIVAZOVA, ICMPNG, LILTO responder, WebServicesPrint  Web BRAdmin Light Strate Windows Mill (Modows utility for printer and print server management through web browser Printer and print server management through web B				
Media Sizes	Media Weights			
Media Sizes  Paper Tray (Standard) Multi-purpose Tray Quitoral Tray Auto Duplex Printing  Width 69.8 to 216 m. mp. th 150 to 46.4 mm A4, ISOBS, A5, ISOB6, Executive Multi-purpose Tray A4, ISOBS, A5, ISOB6, Executive A4, ISOBS, A5, ISOB6, A6,				
Multi-purpose Tray Optional Tray ALTO Duplex Printing SUPPLIANCE ALTO Duplex Printing SUPPLIANCE ALTO Duplex Printing SUPPLIANCE ALTO DUPLEX ALTO DUPL	Media Sizes			
Auto Duplex Printing			Width 69.8 to 216 mm, Le	ngth 116 to 406.4 mm
Windows®   Windows   Windows®   Windows   W				DB6, Executive
Printer Driver  Windows® Windows® Windows® Windows® Actions, NP Professional ACTION, NP Professional Edition, XP Professional XF Edition, Vista Edition, Vista Edition, Server 2003 Server 2003 XeV Edition, Server 2008 Mac OS X 10.39 or greater CDRS printing system (x86, x64 environment)  NETWORK  Protocols  IPV4 (Default)  ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIO'S name resolution, DNS Resolver, mDNS, LLMNR product, PRI-PLD, Custom Raw Pror/Porte100, IPP/IPPS, FTP Server, TELNET Server, HTTP-HTTPS server, SSL/TLS, TFTP client and server, SMTP Combined, PRI-PLD, Custom Raw Pror/Porte100, IPP/IPPS, FTP Server, TELNET Server, HTTP-HTTPS server, SSL/TLS, TFTP client and server, SMTP Combined, PRI-PLD, Custom Raw Pror/Porte100, IPP/IPPS, FTP Server, TELNET Server, HTTP-HTTPS server, SSL/TLS, TFTP Client and server, SMTP Combined, PRI-PLD, Custom Raw Pror/Porte100, IPP/IPPS, FTP Server, TELNET Server, HTTP-HTTPS server, SSL/TLS, TFTP Client and server, SMTP Client, APOP, PD Postore SMTP, SMTP-AUTH, SMMPV1/v2cv3, ICMP, LLTD responder, LPR/LPD, Custom Raw Pror/Porte100, IPP/IPPS, FTP Server, TELNET Server, HTTP-HTTPS server, SSL/TLS, TFTP Client and server, SMTP Client, APOP, PD Postore SMTP, SMTP-AUTH, SMMPV1/v2cv3, ICMP, LLTD responder, LPR/LPD, Custom Raw Pror/Porte100, IPP/IPPS, FTP Server, TELNET Server, HTTP-HTTPS server, SSL/TLS, TFTP Client and server, SMTP Client, APOP, PD Postore SMTP, SMTP-AUTH, SMMPV1/v2cv3, ICMP, LLTD responder, LPR/LPD, Custom Raw Pror/Porte100, IPP/IPPS, FTP Server, TELNET Server, HTTP-HTTPS server, SSL/TLS, TFTP Client and server, SMTP Client, APOP, PD Postore SMTP, SMTP-AUTH,		Auto Duplex Printing	A4	
Macintosh® Linux				
Macind St. 13, 9 or greater	Printer Driver	Windows®		
Linux   CUPS printing system (x86, x64 environment)		Manintanh®		
NETWORK		Macintosn®		
NETWORK   Protocols   IPv4 (Default)   ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS name resolution, DNS Resolver, mDNS, LLMMR responder, LPR/LPD, Custom Raw Port/Port9100, IPP/IPPS, FTP Server, TELNET Server, HTTP/HTTPS server, SSL/TLS, TFTP client and server, SMTP Client, APOP, POP before SMTP, SMTP-AUTH, SMMPV1/v2c/v3, ICMP, LLTD responder, WebServicesPrint NDP, RA, DNS, Soulver, mDNS, LLMMR responder, LPR/LPD, Custom Raw Port/Port910(0, IPP/IPPS, FTP Server, TELNET Server, HTTP/HTTP) Server, SMTP Client, APOP, POP before SMTP, SMTP-AUTH, SNMPv1/v2c/v3, ICMPv6, LLTD responder, WebServicesPrint Web Bradmin Web Bradmin BrAdmin Light Web Braded Management BrAdmin Light Server based management Utility for printer and print server management Server based management utility for printer and print server management Printer and print server management web browser Printer and print server management through web browser Printer and print server management and print server management web provided with the printer and print server management and print server management printer and print server management and prints server management				
Protocols			CUPS printing system (x8	36, x64 environment)
IPP/IPPS, FTP Server, TELNET Server, TETP/HTTPS SERVER, SUTTLS, TFTP client and server, SMTP Client, APOP POP before SMTP, SMTP-AUTH, SNMPv1/v2c/v3, ICMP, LLTD responder, WebServicesPrint    IPv6	INETWORK		CUPS printing system (x8	36, x64 environment)
TFTP client, and server, SMTP Client, APOP,POP before SMTP, SMTP-AUTH, SNMP-1/V2c/v3, ICMP, LLTD responder, WebServicesPrint   NDP, RA, DNS resolver, mDNS, LLMNR responder, LPF/LPD, Custom Raw Port/Port9100, IPP/IPPS, FTP Server, TELNET Server, HTTP/HTTPS STP, SLT/LS, TFTP client and server, SMTP Client, APOP, POP before SMTP, SMTP-AUTH, SNMPV1/v2c/v3, ICMPv6, LLTD responder, WebServicesPrint   Management		Linux	CUPS printing system (xt LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto	16, x64 environment) (x86, x64 environment) IP), WINS/NetBIOS name resolution,
IPv6   NDP, RA, DNS resolver, mDNS, LLMNR responder, WebServicesPrint		Linux	CUPS printing system (x8 LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, I	16, x64 environment) (x86, x64 environment) IP), WINS/NetBIOS name resolution, _PR/LPD, Custom Raw Port/Port9100,
IPv6  NDP, RA, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port/9100, IPp/IPPS, FTP Server, TELNET Server, HTP/HTTPS server, SSL/TLS, TFIP client and server, SMTP Client, APOP, POP before SMTP, SMTP-AUTH, SMMPV1/V2c/v3, ICMPv6, LLTD responder, WebServicesPrint  Management  BRAdmin Professional 3 Web BRAdmin Web BRAdmin Web Based Management BRAdmin Light Driver Deployment Wizard  Server based management Utility Vinidows IS(4,0/5.0) mode only Printer and print server management through web browser Printer and pri		Linux	CUPS printing system (x6 LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, I IPP/IPPS, FTP Server, TELNET Server	16, x64 environment) (x86, x64 environment)  IP), WINS/NetBIOS name resolution, _PR/LPD, Custom Raw Port/Port9100, r, HTTP/HTTPS server, SSL/TLS,
Custom Raw Port/Port910(), IPP/IPPS, FTP Server, TELNET Server, HTP/HTTPS server, SL/TLS, TFTP client and server, SMTP Client, APOP, POP before SMTP, SMTP-AUTH, SNMPV1/v2c/v3, ICMPv6, LLTD responder, WebServicesPrint  Management  BRAdmin Professional 3 Web BRAdmin Web BRAdmin Web BRAdmin Web Based Management Web Based Management BRAdmin Light Driver Deployment Wizard Driver Deployment Driver Ease Amanagement Utility/ Windows IB(A,0/5.0) mode Power Level (Printing / Standby) Driver Deployment Level Driver Deployment Level Driver Deployment Level Driver Deployment Level Driver Driver Based Management D		Linux	CUPS printing system (xt LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, IPP/IPPS, FTP Server, TELNET Serve TFTP client and server, SMTP Client, APC	16, x64 environment) (x86, x64 environment) IP), WINS/NetBIOS name resolution, _PR/LPD, Custom Raw Port/Port9100, -, HTTP/HTTPS server, SSL/TLS, JP,POP before SMTP, SMTP-AUTH,
HTTP/HTTPS server, SSL/TLS, TFTP client and server, SMTP Client, APOP, POP before SMTP, SMTP-AUTH, SMMPv1/v2c/v3, ICMPv6, LLTD responder, WebServicesPrint  Management  BRAdmin Professional 3 Web BRAdmin Web Based Management Web Based Management BRAdmin Web Based Management BRAdmin Light Driver Deployment Wizard  CONSUMABLES  Inbox Toner Standard-Yield Toner TN-3250 Shipped with Standard Yield Standard Yield Toner TN-3290 Approx. 8,000 pages¹  Drum Unit DR-3215 Approx. 25,000 pages (1 page per job)  DIMENSIONS / WEIGHT  Dimensions 371 x 384 x 246 mm 393 x 384 x 259 mm  Weight Average 675W at 25°C  Standby Standby) Scund Pressure Level (Printing / Standby)  Sculp Power Saving Yes  Final Professional 3 Brother original Windows utility for printer and print server management and print server management through web browser Printer and print server management through web browser Printer and print server management through web browser Utility Windows all Macintosh Utility Windows and Macintosh Utility tool for installing a Brother network printer on a networked Windows PC  CONSUMABLES  This approx 3,000 pages (1 page with High-Yield Standard Yield Shipped with High-Yield Standard Yield Toner TN-3290 Approx. 8,000 pages (1 page per job)  DIMENSIONS / WEIGHT  Dimensions 371 x 384 x 246 mm 393 x 384 x 259 mm  Weight 9,5kg  OTHERS  Power Consumption Printing Average 675W at 25°C  Standby Average 675W at 25°C  Noise Sound Pressure Level LpAm= 35 dB (A) / LpA		Linux IPv4 (Default)	CUPS printing system (xt LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, IPP/IPPS, FTP Server, TELNET Serve TFTP client and server, SMTP Client, APC SNMPv1/v2c/v3, ICMP, LLTD re	16, x64 environment) (x86, x64 environment) IP), WINS/NetBIOS name resolution, _PR/LPD, Custom Raw Port/Port9100, _HTTP/HTTPS server, SSL/TLS, _PP,POP before SMTP, SMTP-AUTH, esponder, WebServicesPrint
POP before SMTP, SMTP-AUTH, SMMPu1/v2c/v3, ICMPv6, LLTD responder, WebServicesPrint  Management  BRAdmin Professional 3 Web BRAdmin Web Based Management BRAdmin Light Driver Deployment Wizard  CONSUMABLES  Inbox Toner ITN-3250 Islandard-Yield Toner ITN-3290 Drum Unit DR-3215  DIMENSIONS/WEIGHT Dimensions Weight  OTHERS  Power Consumption Printing Saver based management Utility/ Windows IIS(4,0/5.0) mode only Printer and print server management through web browser BRAdmin Light Printer and print server management through web browser Printer and print server management through web browser Utility tool for installing a Brother network printer on a networked Windows PC  CONSUMABLES  Inbox Toner Shipped with Standard Yield Standard-Yield Toner TN-3250 Approx. 3,000 pages¹ Approx. 3,000 pages¹ Approx. 3,000 pages¹ Approx. 8,000 pages¹ Drum Unit DR-3215 Approx. 25,000 pages (1 page per job)  DIMENSIONS/WEIGHT Dimensions  371 x 384 x 246 mm 393 x 384 x 259 mm  Weight Average 675W at 25°C Standby Standby Standby Average 75W at 25°C Average		Linux IPv4 (Default)	CUPS printing system (x8 LPD/ LPRng printing system (x8 LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, I IPP/IPPS, FTP Server,TELNET Server TFTP client and server, SMTP Client, APC SNMPv1/v2c/v3, ICMP, LLTD re NDP, RA, DNS resolver, mDNS, L	16, x64 environment) (x86, x64 environment) IP), WINS/NetBIOS name resolution, LPR/LPD, Custom Raw Port/Port9100, r, HTTP/HTTPS server, SSL/TLS, DP,POP before SMTP, SMTP-AUTH, ssponder, WebServicesPrint LMNR responder, LPR/LPD,
BRAdmin Professional 3   Brother original Windows utility for printer and print server management Web BRAdmin Web Based Management BRAdmin Light Driver Deployment Wizard Driver Inter and print server management through web browser Printer and print server management operates under Windows and Macintosh Utility tool for installing a Brother network printer on a networked Windows PC    CONSUMABLES		Linux IPv4 (Default)	CUPS printing system (x6 LPD/ LPRng printing system (x6 LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, IPP/IPPS, FTP Server,TELNET Server TFTP client and server, SMTP Client, APC SNMPV1/v2c/v3, ICMP, LLTD re NDP, RA, DNS resolver, mDNS, L Custom Raw Port/Port9100, IPP/IPP Custom Raw Port/Port9100, IPP/IPP	16, x64 environment)  IP), WINS/NetBIOS name resolution, PR/LPD, Custom Raw Port/Port9100, r, HTTP/HTTPS server, SSL/TLS, DP,POP before SMTP, SMTP-AUTH, seponder, WebServicesPrint LMNR responder, LPR/LPD, PS, FTP Server, TELNET Server,
Web BRAdmin Web Based Management BRAdmin Light Driver Deployment Wizard Printer and print server management through web browser BRAdmin Light Driver Deployment Wizard Utility tool for installing a Brother network printer on a networked Windows PC  CONSUMABLES  Inbox Toner Shipped with Standard Yield Shipped with High-Yield Standard-Yield Toner TN-3250 Approx. 3,000 pages¹ Pormu Unit DR-3215 Approx. 25,000 pages¹ Pormu Unit DR-3215 Approx. 25,000 pages (1 page per job)  DIMENSIONS / WEIGHT  Dimensions 371 x 384 x 246 mm 393 x 384 x 259 mm  Weight 9.5kg  OTHERS  Power Consumption Printing Average 675W at 25°C Standby Sleep Average 675W at 25°C Standby Sleep Average 678 wt 25°C Standby Sound Pressure Level (Printing / Standby) Sound Pressure Level (Printing / Standby) Sound Power Saving Yes  Ecology Power Saving Yes		Linux IPv4 (Default)	CUPS printing system (xt LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, I IPP/IPPS, FTP Server, TELNET Serve TFTP client and server, SMTP Client, APC SNMPv1/v2c/v3, ICMP, LLTD re NDP, RA, DNS resolver, mDNS, L Custom Raw Port/Port9100, IPP/IPF HTTP/HTTPS server, SSL/TLS, TFTP client	16, x64 environment) (x86, x64 environment)  IP), WINS/NetBIOS name resolution, _PR/LPD, Custom Raw Port/Port9100, _THTTP/HTTPS server, SSL/TLS, _PP,POP before SMTP, SMTP-AUTH, esponder, WebServicesPrint  LMNR responder, LPR/LPD, _PS, FTP Server, TELNET Server, ent and server, SMTP Client, APOP,
Web Based Management BRAdmin Light Driver Deployment Wizard Printer and print server management through web browser Printer and print server management through web and Macintosh Drowser Printer and print server management operates under Windows and Macintosh Drowser Printer and print server management through web and Macintosh Drowser Printer and print server management operates under Windows And School Printing Printing Printing Standby Shipped with Standard Yield Shipped with Standard Yield Shipped with High-Yield Shipped with High-Yield Shipped with Standard Yield Shipped with High-Yield The Approx. 25,0	Protocols	IPv4 (Default)  IPv6	CUPS printing system (x8 LPD/ LPRng printing system (x8 LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, IPP/IPPS, FTP Server,TELNET Server TFTP client and server, SMTP Client, APC SNMPV1/V2c/v3, ICMP, LLTD r NDP, RA, DNS resolver, mDNS, L Custom Raw Port/Port9100, IPP/IPF HTTP/IHTTPS server, SSL/TLS, TFTP clied POP before SMTP, SMTP-AUTH, SNMPN WebServic	16, x64 environment)  IP), WINS/NetBIOS name resolution, PR/LPD, Custom Raw Port/Port9100, r, HTTP/HTTPS server, SSL/TLS, DP,POP before SMTP, SMTP-AUTH, esponder, WebServicesPrint  LMNR responder, LPR/LPD, PS, FTP Server,TELNET Server, ent and server, SMTP Client, APOP, 1/1/v2c/v3, ICMPv6, LLTD responder, essPrint
BRAdmin Light Driver Deployment Wizard Utility tool for installing a Brother network printer on a networked Windows PC  CONSUMABLES Inbox Toner Shipped with Standard Yield Shipped with High-Yield Standard-Yield Toner TN-3250 Approx. 3,000 pages¹ High-Yield Toner TN-3290 Approx. 8,000 pages¹ Drum Unit DR-3215 Approx. 25,000 pages (1 page per job)  DIMENSIONS / WEIGHT  Dimensions 371 x 384 x 246 mm 393 x 384 x 259 mm  Weight 9.5kg  OTHERS  Power Consumption Printing Average 675W at 25°C Standby Average 75W at 25°C Sleep Average 6W at 25°C Sleep Average 6W at 25°C Sleep Average 6W at 25°C Sound Pressure Level (Printing / Standby) Sound Power Level (Printing / Standby)  Ecology Power Saving Yes Toner Saving Yes	Protocols	IPv4 (Default)  IPv6  BRAdmin Professional 3	CUPS printing system (xt LPD/ LPRng printing system (xt LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, IPP/IPPS, FTP Server, TELNET Server TFTP client and server, SMTP Client, APV SNMPv1/v2c/v3, ICMP, LLTD re NDP, RA, DNS resolver, mDNS, L Custom Raw Port/Port9100, IPP/IPF HTTP/HTTPS server, SSL/TLS, FTP client POP before SMTP, SMTP-AUTH, SMMPWebServic Brother original Windows utility for printing systems.	16, x64 environment) (x86, x64 environment)  IP), WINS/NetBIOS name resolution, _PR/LPD, Custom Raw Port/Port9100, _THTTP/HTTPS server, SSL/TLS, _PP,POP before SMTP, SMTP-AUTH, _asponder, WebServicesPrint  LMNR responder, LPR/LPD, _PS, FTP Server, TELNET Server, _ent and server, SMTP Client, APOP, _11/v2c/v3, ICMPv6, LLTD responder, _essPrint _ter and print server management
Driver Deployment Wizard  Utility tool for installing a Brother network printer on a networked Windows PC  CONSUMABLES  Inbox Toner  Shipped with Standard Yield Shipped with High-Yield Standard-Yield Approx. 3,000 pages¹ High-Yield Toner TN-3290 Approx. 8,000 pages¹ Approx. 8,000 pages¹ Drum Unit DR-3215 Approx. 25,000 pages (1 page per job)  DIMENSIONS / WEIGHT Dimensions Weight 9.5kg  OTHERS  Power Consumption Printing Standby Standby Seep Average 675W at 25°C Standby Average 75W at 25°C Standby Sleep Average 6W at 25°C Noise Sound Pressure Level (Printing / Standby) Sound Power Level (Printing / Standby) Sound Power Level (Printing / Standby) Fool of Standby Sound Power Level (Printing / Standby) Fool of Standby Sund Power Level (Printing / Standby) Fool of Standby Sund Power Level (Printing / Standby) Fool of Standby Fool of Standby Sund Power Level (Printing / Standby) Fool of Standby Fool of	Protocols	IPv4 (Default)  IPv6  BRAdmin Professional 3 Web BRAdmin	CUPS printing system (xi LPD/ LPRng printing system (xi LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, I IPP/IPPS, FTP Server, TELNET Server TFTP client and server, SMTP Client, APC SNMPv1/v2c/v3, ICMP, LLTD rr NDP, RA, DNS resolver, mDNS, L Custom Raw Port/Port9100, IPP/IPF HTTP/HTTPS server, SSL/TLS, TFTP clie POP before SMTP, SMTP-AUTH, SNMPV WebServic Brother original Windows utility for pri	16, x64 environment) (x86, x64 environment)  IP), WINS/NetBIOS name resolution, _PR/LPD, Custom Raw Port/Port9100, , HTTP/HTTPS server, SSL/TLS, )P,POP before SMTP, SMTP-AUTH, esponder, WebServicesPrint  LMNR responder, LPR/LPD, 'S, FTP Server, TELNET Server, ent and server, SMTP Client, APOP, 11/v2c/v3, ICMPv6, LLTD responder, esPrint hter and print server management Windows IIS(4.0/5.0) mode only
CONSUMABLES           Inbox Toner         Shipped with Standard Yield         Shipped with High-Yield           Standard-Yield Toner         TN-3250         Approx. 3,000 pages¹           High-Yield Toner         TN-3290         Approx. 25,000 pages (1 page per job)           DIMENSIONS / WEIGHT           Dimensions         371 x 384 x 246 mm         393 x 384 x 259 mm           Weight         9.5kg           OTHERS           Power Consumption         Printing Standby Standby Standby Sound Pressure Level (Printing / Standby) Sound Power Level (Printing / Standby) Sound Power Level (Printing / Standby)         LpAm= 54 dB (A) / LpAm= 35 dB (A)           Ecology         Power Saving         Yes           Toner Saving         Yes	Protocols	IPv4 (Default)  IPv6  BRAdmin Professional 3 Web BRAdmin Web Based Management	CUPS printing system (xi LPD/ LPRng printing system (xi LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, I IPP/IPPS, FTP Server,TELNET Server TFTP client and server, SMTP Client, APC SNMPV1/v2c/v3, ICMP, LLTD r NDP, RA, DNS resolver, mDNS, L Custom Raw Port/Port9100, IPP/IPF HTTP/HTTPS server, SSL/TLS, TFTP clie POP before SMTP, SMTP-AUTH, SNMPW WebServic Brother original Windows utility for pril Server based management Utility/ N Printer and print server manage	16, x64 environment)  IP), WINS/NetBIOS name resolution, LPR/LPD, Custom Raw Port/Port9100, , HTTP/HTTPS server, SSL/TLS, DP,POP before SMTP, SMTP-AUTH, DESPONDER, WebServicesPrint  LMNR responder, LPR/LPD, PS, FTP Server, TELNET Server, ent and server, SMTP Client, APOP, 11/v2c/v3, ICMPv6, LLTD responder, DESPRINT  ter and print server management Windows IIS(4.0/5.0) mode only ment through web browser
Inbox Toner	Protocols	IPv4 (Default)  IPv6  BRAdmin Professional 3 Web BRAdmin Web Based Management BRAdmin Light	CUPS printing system (xi LPD/ LPRng printing system (xi LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, IPP/IPPS, FTP Server, TELNET Server TFTP client and server, SMTP Client, APV SNMPv1/v2c/v3, ICMP, LLTD re NDP, RA, DNS resolver, mDNS, L Custom Raw Port/Port9100, IPP/IPF HTTP/HTTPS server, SSL/TLS, FTP clie POP before SMTP, SMTP-AUTH, SMMPWebServic Brother original Windows utility for prin Server based management Utility / Printer and print server manage Printer and print server management opens of the server management opens of	16, x64 environment) (x86, x64 environment) (x86, x64 environment)  IP), WINS/NetBIOS name resolution, PR/LPD, Custom Raw Port/Port9100, r, HTTP/HTTPS server, SSL/TLS, PP,POP before SMTP, SMTP-AUTH, asponder, WebServicesPrint  LMNR responder, LPR/LPD, PS, FTP Server,TELNET Server, ent and server, SMTP Client, APOP, 11/v2c/v3, ICMPv6, LLTD responder, essPrint ther and print server management Windows IIS(4.0/5.0) mode only ment through web browser rates under Windows and Macintosh
Standard-Yield Toner         TN-3250         Approx. 3,000 pages¹           High-Yield Toner         TN-3290         Approx. 8,000 pages¹           Drum Unit         DR-3215         Approx. 25,000 pages (1 page per job)           DIMENSIONS / WEIGHT           Dimensions         371 x 384 x 246 mm         393 x 384 x 259 mm           Weight         9.5kg           OTHERS           Power Consumption         Printing         Average 675W at 25°C           Standby         Average 75W at 25°C           Sleep         Average 6W at 25°C           Noise         Sound Pressure Level (Printing / Standby)           Sound Power Level (Printing / Standby)         LWAd= 6.95 B (A) / LWAd= 4.8 B (A)           Ecology         Power Saving         Yes           Toner Saving         Yes	Protocols  Management	IPv4 (Default)  IPv6  BRAdmin Professional 3 Web BRAdmin Web Based Management BRAdmin Light	CUPS printing system (xi LPD/ LPRng printing system (xi LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, IPP/IPPS, FTP Server, TELNET Server TFTP client and server, SMTP Client, APV SNMPv1/v2c/v3, ICMP, LLTD re NDP, RA, DNS resolver, mDNS, L Custom Raw Port/Port9100, IPP/IPF HTTP/HTTPS server, SSL/TLS, FTP clie POP before SMTP, SMTP-AUTH, SMMPWebServic Brother original Windows utility for prin Server based management Utility / Printer and print server manage Printer and print server management opens of the server management opens of	16, x64 environment) (x86, x64 environment) (x86, x64 environment)  IP), WINS/NetBIOS name resolution, PR/LPD, Custom Raw Port/Port9100, r, HTTP/HTTPS server, SSL/TLS, PP,POP before SMTP, SMTP-AUTH, asponder, WebServicesPrint  LMNR responder, LPR/LPD, PS, FTP Server,TELNET Server, ent and server, SMTP Client, APOP, 11/v2c/v3, ICMPv6, LLTD responder, essPrint ther and print server management Windows IIS(4.0/5.0) mode only ment through web browser rates under Windows and Macintosh
High-Yield Toner   TN-3290	Protocols  Management  CONSUMABLES	IPv4 (Default)  IPv6  BRAdmin Professional 3 Web BRAdmin Web Based Management BRAdmin Light	CUPS printing system (xi LPD/ LPRng printing system (xi LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, I IPP/IPPS, FTP Server, TELNET Server TFTP client and server, SMTP Client, APC SNMPv1/v2c/v3, ICMP, LLTD re NDP, RA, DNS resolver, mDNS, L Custom Raw Port/Port9100, IPP/IPF HTTP/HTTPS server, SSL/TLS, TFTP clie POP before SMTP, SMTP-AUTH, SNMPN WebServic Brother original Windows utility for pri Server based management Utility/ Printer and print server manage Printer and print server management ope Utility tool for installing a Brother network.	16, x64 environment) (x86, x64 environment)  IP), WINS/NetBIOS name resolution, _PR/LPD, Custom Raw Port/Port9100, , HTTP/HTTPS server, SSL/TLS, PP,POP before SMTP, SMTP-AUTH, esponder, WebServicesPrint  LMNR responder, LPR/LPD, PS, FTP Server, TELNET Server, ent and server, SMTP Client, APOP, r1/v2c/v3, ICMPv6, LLTD responder, esPrint nter and print server management Windows IIS(4.0/5.0) mode only ment through web browser rates under Windows and Macintosh printer on a networked Windows PC
DIMENSIONS / WEIGHT           Dimensions         371 x 384 x 246 mm         393 x 384 x 259 mm           Weight         9.5kg           OTHERS           Power Consumption         Printing Average 675W at 25°C Average 75W at 25°C Average 6W at 25°C Average 6W at 25°C           Noise         Sound Pressure Level (Printing / Standby) Sound Power Level (Printing / Standby)         LpAm= 54 dB (A) / LpAm= 35 dB (A)           Ecology         Power Saving         Yes           Toner Saving         Yes	Protocols  Management  CONSUMABLES Inbox Toner Standard-Yield Toner	IPv4 (Default)  IPv6  BRAdmin Professional 3 Web BRAdmin Web Based Management BRAdmin Light Driver Deployment Wizard  TN-3250	CUPS printing system (xt LPD/ LPRng printing system (xt LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, IPP/IPPS, FTP Server, TELNET Server TFTP client and server, SMTP Client, APC SNMPv1/v2c/v3, ICMP, LLTD re NDP, RA, DNS resolver, mDNS, L Custom Raw Port/Port9100, IPP/IPF HTTP/HTTPS server, SSL/TLS, TFTP client POP before SMTP, SMTP-AUTH, SMMPN WebServic Brother original Windows utility for prin Server based management Utility / Printer and print server manage Printer and print server management ope Utility tool for installing a Brother network Shipped with Standard Yield Approx. 3,00	16, x64 environment) (x86, x64 environment)  IP), WINS/NetBIOS name resolution, PR/LPD, Custom Raw Port/Port9100, r, HTTP/HTTPS server, SSL/TLS, DP,POP before SMTP, SMTP-AUTH, esponder, WebServicesPrint  LMNR responder, LPR/LPD, PS, FTP Server,TELNET Server, ent and server, SMTP Client, APOP, r1/v2c/v3, ICMPv6, LLTD responder, essPrint ther and print server management Windows IIS(4.0/5.0) mode only ment through web browser rates under Windows and Macintosh printer on a networked Windows PC  Shipped with High-Yield 0 pages¹
Dimensions         371 x 384 x 246 mm         393 x 384 x 259 mm           Weight         9.5 kg           OTHERS           Power Consumption         Printing Standby Standby Sleep         Average 675W at 25°C Average 75W at 25°C Average 6W at 25°C           Noise         Sound Pressure Level (Printing / Standby) Sound Power Level (Printing / Standby)         LpAm= 54 dB (A) / LpAm= 35 dB (A) / LpAm= 35 dB (A)           Ecology         Power Saving         Yes           Toner Saving         Yes           Yes	Protocols  Management  CONSUMABLES Inbox Toner Standard-Yield Toner High-Yield Toner	IPv4 (Default)  IPv6  BRAdmin Professional 3 Web BRAdmin Web Based Management BRAdmin Light Driver Deployment Wizard  TN-3250 TN-3290	CUPS printing system (x8 LPD/ LPRng printing system (x8 LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, I IPP/IPPS, FTP Server, TELNET Server TFTP client and server, SMTP Client, APC SNMPv1/v2c/v3, ICMP, LLTD re NDP, RA, DNS resolver, mDNS, L Custom Raw Port/Port9100, IPP/IPF HTTP/HTTPS server, SSL/TLS, TFTP clie POP before SMTP, SMTP-AUTH, SNMPN WebServic Brother original Windows utility for pri Server based management Utility/ Printer and print server manage Printer and print server manage Printer and print server manage Printer and print server management ope Utility tool for installing a Brother network Shipped with Standard Yield  Approx. 3,00 Approx. 3,00	16, x64 environment) (x86, x64 environment)  IP), WINS/NetBIOS name resolution, _PR/LPD, Custom Raw Port/Port9100, , HTTP/HTTPS server, SSL/TLS, _PP,POP before SMTP, SMTP-AUTH, esponder, WebServicesPrint  LMNR responder, LPR/LPD, _PS, FTP Server, TELNET Server, ent and server, SMTP Client, APOP, _11/v2c/v3, ICMPv6, LLTD responder, _esPrint her and print server management Windows IIS(4.0/5.0) mode only ment through web browser rates under Windows and Macintosh printer on a networked Windows PC  Shipped with High-Yield  0 pages¹ 0 pages¹ 0 pages¹
Weight         9.5kg           OTHERS           Power Consumption         Printing Standby Sleep         Average 675W at 25°C Average 75W at 25°C Average 6W at 25°C           Noise         Sound Pressure Level (Printing / Standby) Sound Power Level (Printing / Standby)         LpAm= 54 dB (A) / LpAm= 35 dB (A) (Printing / Standby)           Ecology         Power Saving Toner Saving         Yes           Toner Saving         Yes	Protocols  Management  CONSUMABLES Inbox Toner Standard-Yield Toner High-Yield Toner	IPv4 (Default)  IPv6  BRAdmin Professional 3 Web BRAdmin Web Based Management BRAdmin Light Driver Deployment Wizard  TN-3250 TN-3290	CUPS printing system (x8 LPD/ LPRng printing system (x8 LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, I IPP/IPPS, FTP Server, TELNET Server TFTP client and server, SMTP Client, APC SNMPv1/v2c/v3, ICMP, LLTD re NDP, RA, DNS resolver, mDNS, L Custom Raw Port/Port9100, IPP/IPF HTTP/HTTPS server, SSL/TLS, TFTP clie POP before SMTP, SMTP-AUTH, SNMPN WebServic Brother original Windows utility for pri Server based management Utility/ Printer and print server manage Printer and print server manage Printer and print server manage Printer and print server management ope Utility tool for installing a Brother network Shipped with Standard Yield  Approx. 3,00 Approx. 3,00	16, x64 environment) (x86, x64 environment)  IP), WINS/NetBIOS name resolution, _PR/LPD, Custom Raw Port/Port9100, , HTTP/HTTPS server, SSL/TLS, _PP,POP before SMTP, SMTP-AUTH, esponder, WebServicesPrint  LMNR responder, LPR/LPD, _PS, FTP Server, TELNET Server, ent and server, SMTP Client, APOP, _11/v2c/v3, ICMPv6, LLTD responder, _esPrint her and print server management Windows IIS(4.0/5.0) mode only ment through web browser rates under Windows and Macintosh printer on a networked Windows PC  Shipped with High-Yield  0 pages¹ 0 pages¹ 0 pages¹
OTHERS           Power Consumption         Printing Standby Standby Average 675W at 25°C Average 75W at 25°C Sleep Average 6W at 25°C           Noise         Sound Pressure Level (Printing / Standby) Sound Power Level (Printing / Standby)         LpAm= 54 dB (A) / LpAm= 35 dB (A)           Ecology         Power Saving Toner Saving Yes         Yes	Protocols  Management  CONSUMABLES Inbox Toner Standard-Yield Toner High-Yield Toner Drum Unit	IPv4 (Default)  IPv6  BRAdmin Professional 3 Web BRAdmin Web Based Management BRAdmin Light Driver Deployment Wizard  TN-3250 TN-3290	CUPS printing system (x8 LPD/ LPRng printing system (x8 LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, I IPP/IPPS, FTP Server, TELNET Server TFTP client and server, SMTP Client, APC SNMPv1/v2c/v3, ICMP, LLTD re NDP, RA, DNS resolver, mDNS, L Custom Raw Port/Port9100, IPP/IPF HTTP/HTTPS server, SSL/TLS, TFTP clie POP before SMTP, SMTP-AUTH, SNMPN WebServic Brother original Windows utility for pri Server based management Utility/ Printer and print server manage Printer and print server manage Printer and print server manage Printer and print server management ope Utility tool for installing a Brother network Shipped with Standard Yield  Approx. 3,00 Approx. 3,00	16, x64 environment) (x86, x64 environment) (x86, x64 environment)  IP), WINS/NetBIOS name resolution, _PR/LPD, Custom Raw Port/Port9100, , HTTP/HTTPS server, SSL/TLS, )P,POP before SMTP, SMTP-AUTH, esponder, WebServicesPrint  LMNR responder, LPR/LPD, 95, FTP Server, TELNET Server, ent and server, SMTP Client, APOP, 11/v2c/v3, ICMPv6, LLTD responder, esPrint nter and print server management Vindows IIS(4.0/5.0) mode only ment through web browser rates under Windows and Macintosh printer on a networked Windows PC  Shipped with High-Yield 0 pages¹ 0 pages¹
Power Consumption     Printing Standby     Average 675W at 25°C Average 75W at 25°C       Noise     Sound Pressure Level (Printing / Standby) Sound Power Level (Printing / Standby)     LpAm= 54 dB (A) / LpAm= 35 dB (A)       Ecology     LWAd= 6.95 B (A) / LWAd= 4.8 B (A)       Ecology     Power Saving Toner Saving     Yes Yes	Protocols  Management  CONSUMABLES Inbox Toner Standard-Yield Toner High-Yield Toner Drum Unit Dimensions / WEIGHT Dimensions	IPv4 (Default)  IPv6  BRAdmin Professional 3 Web BRAdmin Web Based Management BRAdmin Light Driver Deployment Wizard  TN-3250 TN-3290	CUPS printing system (xt LPD/ LPRng printing system (xt LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, IPP/IPPS, FTP Server, TELNET Server TFTP client and server, SMTP Client, APC SNMPv1/v2c/v3, ICMP, LLTD re NDP, RA, DNS resolver, mDNS, L Custom Raw Port/Port9100, IPP/IPF HTTP/HTTPS server, SSL/TLS, TFTP client POP before SMTP, SMTP-AUTH, SMMPN WebServic Brother original Windows utility for prin Server based management Utility / Printer and print server manage Printer and print server management ope Utility tool for installing a Brother network Shipped with Standard Yield  Approx. 3,00 Approx. 25,000 pages 371 x 384 x 246 mm	16, x64 environment) (x86, x64 environment) (x86, x64 environment)  IP), WINS/NetBIOS name resolution, PR/LPD, Custom Raw Port/Port9100, r, HTTP/HTTPS server, SSL/TLS, DP,POP before SMTP, SMTP-AUTH, esponder, WebServicesPrint  LMNR responder, LPR/LPD, PS, FTP Server,TELNET Server, ent and server, SMTP Client, APOP, 11/v2c/v3, ICMPv6, LLTD responder, esePrint ther and print server management Windows IIS(4.0/5.0) mode only ment through web browser rates under Windows and Macintosh printer on a networked Windows PC  Shipped with High-Yield 0 pages¹ 0 pages¹ 0 tpage per job)
Standby	Protocols  Management  CONSUMABLES Inbox Toner Standard-Yield Toner High-Yield Toner Drum Unit DIMENSIONS / WEIGHT Dimensions Weight	IPv4 (Default)  IPv6  BRAdmin Professional 3 Web BRAdmin Web Based Management BRAdmin Light Driver Deployment Wizard  TN-3250 TN-3290	CUPS printing system (xt LPD/ LPRng printing system (xt LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, IPP/IPPS, FTP Server, TELNET Server TFTP client and server, SMTP Client, APC SNMPv1/v2c/v3, ICMP, LLTD re NDP, RA, DNS resolver, mDNS, L Custom Raw Port/Port9100, IPP/IPF HTTP/HTTPS server, SSL/TLS, TFTP client POP before SMTP, SMTP-AUTH, SMMPN WebServic Brother original Windows utility for prin Server based management Utility / Printer and print server manage Printer and print server management ope Utility tool for installing a Brother network Shipped with Standard Yield  Approx. 3,00 Approx. 25,000 pages 371 x 384 x 246 mm	16, x64 environment) (x86, x64 environment) (x86, x64 environment)  IP), WINS/NetBIOS name resolution, PR/LPD, Custom Raw Port/Port9100, r, HTTP/HTTPS server, SSL/TLS, DP,POP before SMTP, SMTP-AUTH, esponder, WebServicesPrint  LMNR responder, LPR/LPD, PS, FTP Server,TELNET Server, ent and server, SMTP Client, APOP, 11/v2c/v3, ICMPv6, LLTD responder, esePrint ther and print server management Windows IIS(4.0/5.0) mode only ment through web browser rates under Windows and Macintosh printer on a networked Windows PC  Shipped with High-Yield 0 pages¹ 0 pages¹ 0 tpage per job)
Sleep	Protocols  Management  CONSUMABLES Inbox Toner Standard-Yield Toner High-Yield Toner Drum Unit DIMENSIONS / WEIGHT Dimensions Weight OTHERS	IPv4 (Default)  IPv6  BRAdmin Professional 3 Web BRAdmin Web Based Management BRAdmin Light Driver Deployment Wizard  TN-3250 TN-3290 DR-3215	CUPS printing system (x8 LPD/ LPRng printing system (x8 LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, I IPP/IPPS, FTP Server, TELNET Server TFTP client and server, SMTP Client, APC SNMPv1/v2c/v3, ICMP, LLTD re NDP, RA, DNS resolver, mDNS, L Custom Raw Port/Port9100, IPP/IPF HTTP/HTTPS server, SSL/TLS, TFTP clie POP before SMTP, SMTP-AUTH, SNMPW WebServic Brother original Windows utility for printer and print server manage Printer and print server management ope Utility tool for installing a Brother network Shipped with Standard Yield  Approx. 3,00 Approx. 3,00 Approx. 25,000 pages	16, x64 environment) (x86, x64 environment) (x97, x64, x64 environment) (x97, x64, x64 environment) (x97, x64, x64 environment) (x98, x64
Noise         Sound Pressure Level (Printing / Standby)         LpAm= 54 dB (A) / LpAm= 35 dB (A)           Sound Power Level (Printing / Standby)         LWAd= 6.95 B (A) / LWAd= 4.8 B (A)           Ecology         Power Saving Toner Saving         Yes           Yes         Yes	Protocols  Management  CONSUMABLES Inbox Toner Standard-Yield Toner High-Yield Toner Drum Unit DIMENSIONS / WEIGHT Dimensions Weight OTHERS	IPv4 (Default)  IPv6  BRAdmin Professional 3 Web BRAdmin Web Based Management BRAdmin Light Driver Deployment Wizard  TN-3250 TN-3290 DR-3215	CUPS printing system (x8 LPD/ LPRng printing system (x8 LPP/ LPRng printing system (x8 LPRng prin	16, x64 environment) (x86, x64 environment) (x96, x64 environment) (
(Printing / Standby) Sound Power Level (Printing / Standby)  Ecology Power Saving Toner Saving Yes Toner Saving Yes	Protocols  Management  CONSUMABLES Inbox Toner Standard-Yield Toner High-Yield Toner Drum Unit DIMENSIONS / WEIGHT Dimensions Weight OTHERS	IPv4 (Default)  IPv6  BRAdmin Professional 3 Web BRAdmin Web Based Management BRAdmin Light Driver Deployment Wizard  TN-3250 TN-3290 DR-3215  Printing Standby	CUPS printing system (xt LPD/ LPRng printing system (xt LPD/ L	16, x64 environment) (x86, x64 environment) (x86, x64 environment)  IP), WINS/NetBIOS name resolution, PR/LPD, Custom Raw Port/Port9100, r, HTTP/HTTPS server, SSL/TLS, DP,POP before SMTP, SMTP-AUTH, esponder, WebServicesPrint  LMNR responder, LPR/LPD, PS, FTP Server, TELNET Server, ent and server, SMTP Client, APOP, 11/v2c/v3, ICMPv6, LLTD responder, essPrint enter and print server management Windows IIS(4.0/5.0) mode only ment through web browser rates under Windows and Macintosh printer on a networked Windows PC  Shipped with High-Yield 0 pages¹ 0 pages¹ 0 pages¹ 1 page per job)  393 x 384 x 259 mm 3
Sound Power Level LWAd= 6.95 B (A) / LWAd= 4.8 B (A) (Printing / Standby)  Ecology Power Saving Yes Toner Saving Yes	Protocols  Management  CONSUMABLES Inbox Toner Standard-Yield Toner High-Yield Toner Drum Unit  DIMENSIONS / WEIGHT Dimensions Weight  OTHERS Power Consumption	Linux  IPv4 (Default)  IPv6  BRAdmin Professional 3 Web BRAdmin Web Based Management BRAdmin Light Driver Deployment Wizard  TN-3250 TN-3290 DR-3215  Printing Standby Sleep	CUPS printing system (x8 LPD/ LPRng printing system (x8 LPD/ L	16, x64 environment) (x86, x64 environment) (x97, x97, x97, x97, x97, x97, x97, x97,
Ecology Power Saving Yes Toner Saving Yes	Protocols  Management  CONSUMABLES Inbox Toner Standard-Yield Toner High-Yield Toner Drum Unit DIMENSIONS / WEIGHT Dimensions Weight OTHERS Power Consumption	IPv4 (Default)  IPv6  BRAdmin Professional 3 Web BRAdmin Web Based Management BRAdmin Light Driver Deployment Wizard  TN-3250 TN-3290 DR-3215  Printing Standby Sleep Sound Pressure Level	CUPS printing system (x8 LPD/ LPRng printing system (x8 LPD/ L	16, x64 environment) (x86, x64 environment) (x97, x97, x97, x97, x97, x97, x97, x97,
Toner Saving Yes	Protocols  Management  CONSUMABLES Inbox Toner Standard-Yield Toner High-Yield Toner Drum Unit DIMENSIONS / WEIGHT Dimensions Weight OTHERS Power Consumption	IPv4 (Default)  IPv6  BRAdmin Professional 3 Web BRAdmin Web Based Management BRAdmin Light Driver Deployment Wizard  TN-3250 TN-3290 DR-3215  Printing Standby Sleep Sound Pressure Level (Printing / Standby)	CUPS printing system (x8 LPD/ LPRng printing system (x8 LPD/ LPR) (x8 LPR) (x	16, x64 environment) (x86, x64 environment) (x86, x64 environment)  IP), WINS/NetBIOS name resolution, PR/LPD, Custom Raw Port/Port9100, r, HTTP/HTTPS server, SSL/TLS, DP,POP before SMTP, SMTP-AUTH, esponder, WebServicesPrint  LMNR responder, LPR/LPD, PS, FTP Server, TELNET Server, ent and server, SMTP Client, APOP, r1/v2c/v3, ICMPv6, LLTD responder, essPrint ther and print server management Windows IIS(4.0/5.0) mode only ment through web browser rates under Windows and Macintosh printer on a networked Windows PC  Shipped with High-Yield 0 pages¹ 0 pages¹ 10 pages¹ 11 page per job)  393 x 384 x 259 mm 12 SerC 14 at 25°C 15 ct 25°C 16 at 25°C 17 ct 25°C 18 ct 25°C
	Protocols  Management  CONSUMABLES Inbox Toner Standard-Yield Toner High-Yield Toner Drum Unit  DIMENSIONS / WEIGHT Dimensions Weight OTHERS Power Consumption  Noise	IPv4 (Default)  IPv6  BRAdmin Professional 3 Web BRAdmin Web Based Management BRAdmin Light Driver Deployment Wizard  TN-3250 TN-3290 DR-3215  Printing Standby Sleep Sound Pressure Level (Printing / Standby) Sound Power Level (Printing / Standby)	CUPS printing system (x8 LPD/ LPRng printing system (x8 LPD/ LPRng printing system ARP, RARP, BOOTP, DHCP, APIPA(Auto DNS Resolver, mDNS, LLMNR responder, I IPP/IPPS, FTP Server, TELNET Server TFTP client and server, SMTP Client, APC SNMPv1/v2c/v3, ICMP, LLTD re NDP, RA, DNS resolver, mDNS, L Custom Raw Port/Port9100, IPP/IPF HTTP/HTTPS server, SSL/TLS, TFTP client POP before SMTP, SMTP-AUTH, SNMPv WebServic Brother original Windows utility for prints Server based management Utility/ Printer and print server manage Printer and print server manage Printer and print server management ope Utility tool for installing a Brother network Shipped with Standard Yield  Approx. 3,00 Approx. 8,00 Approx. 25,000 pages 371 x 384 x 246 mm  9.5kg  Average 675V Average 75W Average 675V Average 75W Average 54 dB (A) / L LWAd= 6.95 B (A) / L	16, x64 environment) (x86, x64 environment) (x86, x64 environment)  IP), WINS/NetBIOS name resolution, _PR/LPD, Custom Raw Port/Port9100, _, HTTP/HTTPS server, SSL/TLS, _PPOP before SMTP, SMTP-AUTH, _esponder, WebServicesPrint  LMNR responder, LPR/LPD, _S, FTP Server, TELNET Server, _ent and server, SMTP Client, APOP, _11/v2c/v3, ICMPv6, LLTD responder, _esPrintnter and print server management _Windows IIS(4.0/5.0) mode onlyment through web browserrates under Windows and Macintoshprinter on a networked Windows PC
	Protocols  Management  CONSUMABLES Inbox Toner Standard-Yield Toner High-Yield Toner Drum Unit  DIMENSIONS / WEIGHT Dimensions Weight OTHERS Power Consumption  Noise	Linux  IPv4 (Default)  IPv6  BRAdmin Professional 3 Web BRAdmin Web Based Management BRAdmin Light Driver Deployment Wizard  TN-3250 TN-3290 DR-3215  Printing Standby Sleep Sound Pressure Level (Printing / Standby) Sound Power Level (Printing / Standby) Power Saving	CUPS printing system (x8 LPD/ LPRng printing system (x8 LPD/ L	16, x64 environment) (x86, x64 environment) (x86, x64 environment)  IP), WINS/NetBIOS name resolution, PR/LPD, Custom Raw Port/Port9100, r, HTTP/HTTPS server, SSL/TLS, DP,POP before SMTP, SMTP-AUTH, asponder, WebServicesPrint  LMNR responder, LPR/LPD, DS, FTP Server, TELNET Server, ent and server, SMTP Client, APOP, r1/v2c/v3, ICMPv6, LLTD responder, essPrint enter and print server management Windows IIS(4.0/5.0) mode only ment through web browser rates under Windows and Macintosh printer on a networked Windows PC  Shipped with High-Yield D pages¹ D pages¹ D pages¹ D pages¹ D pages¹ D pages 1 D pages 1 D pages 3 D pages 4 D pages 5 D pages 5 D pages 6 D pages 6 D pages 7 D pages 9 D pages 9 D pages 9 D pages 9 D pages 1 D pages 1 D pages 1 D pages 3 D pages 3 D pages 3 D pages 3 D pages 4 D pages 4 D pages 5 D pages 5 D pages 6 D pages 6 D pages 7 D pages 7 D pages 8 D pages 9 D page




















1 In accordance with ISO/IEC 19752 <sup>2</sup> 13 sides per minute, 6.5 sheets per minute (A4)

Brother strongly recommends the use of genuine Brother consumable products only. Benefits include better quality prints, greater yields per consumable, protection of your machine from damages and achievement of optimum performance. As a precaution, please note that your machine warranty may not cover any damages arising from the use of non-genuine consumables.

For more information regarding systems requirements, please visit http://solutions.brother.com